

SPROULE MANUFACTURING COMPANY, INC. HIGH TEMPERATURE PRE-MOLDED FITTING COVERS

Effective: 7/2008

90° Screwed / Socket Weld Elbows Price List



SINGLE LAYER INSULATION THICKNESS							
IPS	1"	1 1/2"	2"	2 1/2"	3"	3 1/2"	4"
1/2"	\$ 6.40	\$ 7.88	\$ 10.36	\$ 13.49	\$ 21.07	\$ 28.80	\$ 39.48
3/4"	\$ 6.46	\$ 7.97	\$ 10.68	\$ 13.66	\$ 21.12	\$ 29.12	\$ 39.72
1"	\$ 6.69	\$ 8.44	\$ 11.74	\$ 14.30	\$ 20.56	\$ 30.00	\$ 39.91
1 1/4"	\$ 6.37	\$ 8.87	\$ 12.53	\$ 14.92	\$ 20.51	\$ 31.12	\$ 42.39
1 1/2"	\$ 7.32	\$ 9.43	\$ 13.32	\$ 18.62	\$ 26.37	\$ 32.63	\$ 44.63
2"	\$ 8.19	\$ 9.41	\$ 13.96	\$ 18.00	\$ 26.77	\$ 33.58	\$ 44.66
2 1/2"	\$ 9.36	\$ 11.42	\$ 15.44	\$ 23.85	\$ 32.86	\$ 42.25	\$ 53.05
3"	\$ 10.47	\$ 13.09	\$ 16.85	\$ 21.55	\$ 30.58	\$ 42.81	\$ 53.64
3 1/2"		\$ 16.58	\$ 21.66	\$ 22.53	\$ 35.31	\$ 48.57	
4"		\$ 16.90	\$ 23.49	\$ 27.06	\$ 31.53	\$ 45.76	

Please Note: All Sproule High Temperature Pre-Molded Screwed / Socket Weld Fitting Covers will fit Standard 3000# Socket Weld and 150# Malleable Iron Screwed elbows. For Schedule 80, 6000# Socket Welds, or 125# Cast Iron Screwed Fittings please refer to the Heavy Walled Screwed / Socket Weld Fittings Cover price list on page 15.

Packaging Data

INSULATION THICKNESS							
IPS	1"	1 1/2"	2"	2 1/2"	3"	3 1/2"	4"
1/2"	48 - A - 9	20 - A - 11	18 - B - 21	14 - B - 31	12 - C - 41	8 - C - 36	6 - C - 37
3/4"	48 - A - 8	20 - A - 10	18 - B - 21	14 - B - 30	12 - C - 41	8 - C - 36	6 - C - 37
1"	30 - A - 9	15 - A - 11	16 - B - 24	14 - B - 30	10 - C - 34	10 - C - 44	6 - C - 37
1 1/4"	25 - A - 6	18 - B - 15	16 - B - 24	14 - B - 24	12 - C - 39	8 - C - 35	6 - C - 36
1 1/2"	20 - A - 8	18 - B - 14	14 - B - 26	12 - C - 39	10 - C - 43	6 - C - 36	4 - C - 33
2"	15 - A - 8	16 - B - 16	14 - B - 24	12 - C - 29	10 - C - 41	6 - C - 35	4 - C - 32
2 1/2"	18 - B - 13	14 - B - 22	12 - C - 31	8 - C - 27	6 - C - 34	4 - C - 31	4 - C - 35
3"	16 - B - 14	14 - B - 21	12 - C - 27	8 - C - 25	6 - C - 32	5 - C - 37	4 - C - 33
3 1/2"		12 - C - 29	8 - C - 32	6 - C - 25	4 - C - 28	5 - C - 40	
4"		12 - C - 28	8 - C - 29	6 - C - 22	4 - C - 26	3 - C - 23	

KEY: Quantity Per Carton - Carton Type - Weight Per Carton

Please refer to the *General Packaging Data* on page 17 for detailed box and shipping information.

All of the sizes listed above may not necessarily be available. Please call 1-800-628-6998, or visit www.sproule-mfg.com for a list of sizes currently available.

1-800-628-6998 ~ www.sproule-mfg.com

3239 Phoenixville Pike, Devault PA 19432 USA ~ Phone: (610) 647-5687 ~ Fax: (610) 647-7146 ~ email: devault@sproule-mfg.com
2260 Appelt Drive, Houston, TX 77015 USA ~ Phone: (281) 860-9950 ~ Fax: (281) 860-9978 ~ email: houston@sproule-mfg.com

**SPROULE MANUFACTURING COMPANY, INC.
HIGH TEMPERATURE PRE-MOLDED FITTING COVERS**

Effective: 7/2008

**90° Screwed / Socket Weld Elbows
WeatherJac™ Compatibility Chart**



Sproule Mfg. guarantees the fit of all WeatherJacs™ when used in conjunction with Sproule High Temperature Pre-Molded Fitting Covers.


INSULATION THICKNESS							
IPS	1"	1 1/2"	2"	2 1/2"	3"	3 1/2"	4"
1/2"	2	5	8	12	23	59	60
3/4"	2	5	8	12	23	59	60
1"	3	6	11	12	23	59	60
1 1/4"	3	8	11	18	23	59	60
1 1/2"	5	8	12	23	59	60	
2"	6	11	12	23	59	60	
2 1/2"	8	12	23	59	60	61	
3"	11	12	23	59	60	61	
3 1/2"	12	23	59	60	61		
4"	12	23	59	60	61		

Bold sizes vary from published charts of other major elbow manufacturers.

Single number sizes are available as Sproule Mfg. Co., Inc. Numbered WeatherJacs™ as well as standard numbered fitting from other major metal elbow manufacturers.

90° Screwed / Socket Weld Elbows Details

* **Please Note:** Preformed Aluminum Jackets in bold print vary from the recommended sizes published by the major aluminum elbow manufacturers. Sproule Mfg. Co., Inc. must maintain a minimum thickness in the heel for structural integrity of the Pre-Molded Fitting Cover. The diagram below highlights the area in which the wall thickness can be no less than 1/8" thick. This stringent specification requires that we change our 'outside mold' to guarantee the 1/8" wall thickness while still maintaining the proper Outside Diameter (OD) set forth in ASTM C 585. Therefore, the new 'outside mold' changes the recommended aluminum elbow for the given Pre-Molded Fitting Covers.



All of the sizes listed above may not necessarily be available. Please call 1-800-628-6998, or visit www.sproule-mfg.com for a list of sizes currently available.

1-800-628-6998 ~ www.sproule-mfg.com

3239 Phoenixville Pike, Devault PA 19432 USA ~ Phone: (610) 647-5687 ~ Fax: (610) 647-7146 ~ email: devault@sproule-mfg.com
2260 Appelt Drive, Houston, TX 77015 USA ~ Phone: (281) 860-9950 ~ Fax: (281) 860-9978 ~ email: houston@sproule-mfg.com